

"ALL STAINLESS" SANITARY PRESSURE GAUGE, TYPE PBQ

TYPE	DRAWING	DIMENSIONS mm																																																												
18 19	<p>ISO 2852 Tri - Clamp</p> <p>For pipes per ISO 2037 and BS 4825 Part 1</p>	<table border="1"> <thead> <tr> <th>DN</th> <th>PN bar</th> <th>D</th> <th>dM</th> <th>For tube Male ø</th> <th>Tube Female ø</th> </tr> </thead> <tbody> <tr> <td>DN25 - 1"</td> <td rowspan="3">40</td> <td>50.5</td> <td>21</td> <td>25 x 1,2</td> <td>22,6</td> </tr> <tr> <td>DN38 - 1 1/2"</td> <td>64</td> <td>32</td> <td>38 x 1,2</td> <td>35,6</td> </tr> <tr> <td>DN51 - 2"</td> <td>77.5</td> <td>46</td> <td>51 x 1,2</td> <td>48,6</td> </tr> <tr> <td>DN63,5 - 2 1/2"</td> <td rowspan="2">25</td> <td>91</td> <td>56</td> <td>63,5 x 1,6</td> <td>60,3</td> </tr> <tr> <td>DN76,1 - 3"</td> <td>91</td> <td>66</td> <td>76,1 x 1,6</td> <td>72,9</td> </tr> </tbody> </table>	DN	PN bar	D	dM	For tube Male ø	Tube Female ø	DN25 - 1"	40	50.5	21	25 x 1,2	22,6	DN38 - 1 1/2"	64	32	38 x 1,2	35,6	DN51 - 2"	77.5	46	51 x 1,2	48,6	DN63,5 - 2 1/2"	25	91	56	63,5 x 1,6	60,3	DN76,1 - 3"	91	66	76,1 x 1,6	72,9																											
			DN	PN bar	D	dM	For tube Male ø	Tube Female ø																																																						
DN25 - 1"	40	50.5	21	25 x 1,2	22,6																																																									
DN38 - 1 1/2"		64	32	38 x 1,2	35,6																																																									
DN51 - 2"		77.5	46	51 x 1,2	48,6																																																									
DN63,5 - 2 1/2"	25	91	56	63,5 x 1,6	60,3																																																									
DN76,1 - 3"		91	66	76,1 x 1,6	72,9																																																									
181 182 183	<p>DIN 32 676 Tri - Clamp</p> <p>For pipes per DIN 11 850</p>	<table border="1"> <thead> <tr> <th>NPS</th> <th>PN bar</th> <th>D</th> <th>dM</th> <th>For tube Male ø</th> <th>Tube Female ø</th> </tr> </thead> <tbody> <tr> <td>DN 25</td> <td rowspan="4">40</td> <td rowspan="4">50,5</td> <td>24</td> <td>29 x 1,5</td> <td>26</td> </tr> <tr> <td>DN 32</td> <td>28</td> <td>35 x 1,5</td> <td>32</td> </tr> <tr> <td>DN 40</td> <td>32</td> <td>41 x 1,5</td> <td>38</td> </tr> <tr> <td>DN 50</td> <td>46</td> <td>53 x 1,5</td> <td>50</td> </tr> <tr> <td>DN 65</td> <td>25</td> <td>91</td> <td>60</td> <td>70 x 2</td> <td>66</td> </tr> </tbody> </table>	NPS	PN bar	D	dM	For tube Male ø	Tube Female ø	DN 25	40	50,5	24	29 x 1,5	26	DN 32	28	35 x 1,5	32	DN 40	32	41 x 1,5	38	DN 50	46	53 x 1,5	50	DN 65	25	91	60	70 x 2	66																														
			NPS	PN bar	D	dM	For tube Male ø	Tube Female ø																																																						
DN 25	40	50,5	24	29 x 1,5	26																																																									
DN 32			28	35 x 1,5	32																																																									
DN 40			32	41 x 1,5	38																																																									
DN 50			46	53 x 1,5	50																																																									
DN 65	25	91	60	70 x 2	66																																																									
191 192 193	<p>BS 4825 Tri - Clamp</p> <p>For pipes per BS 4825 part 3 or ASME BPE</p>	<table border="1"> <thead> <tr> <th rowspan="2">ASME BPE</th> <th rowspan="2">BS4825 - ISO 1127</th> <th colspan="4">For tubes according to:</th> <th colspan="2">ASME BPE</th> <th colspan="2">ISO 1127</th> </tr> <tr> <th>NPS</th> <th>DN</th> <th>PN bar</th> <th>D</th> <th>dM</th> <th>Tube Male ø</th> <th>Tube Female ø</th> <th>Tube Male ø</th> <th>Tube Female ø</th> </tr> </thead> <tbody> <tr> <td rowspan="5">40</td> <td>3/4"</td> <td>20</td> <td>25,4</td> <td>16</td> <td>19,05 x 1,2</td> <td>16,65</td> <td>26,9 x 1,6</td> <td>23,7</td> </tr> <tr> <td>1"</td> <td>25</td> <td>50,5</td> <td>21</td> <td>25,4 x 1,6</td> <td>22,2</td> <td>33,7 x 2</td> <td>29,7</td> </tr> <tr> <td>1 1/2"</td> <td>38</td> <td>64</td> <td>30</td> <td>38,1 x 1,6</td> <td>34,8</td> <td>42,4 x 2</td> <td>38,4</td> </tr> <tr> <td>2"</td> <td>51</td> <td>77,5</td> <td>38</td> <td>50,8 x 1,6</td> <td>47,5</td> <td>48,3 x 2</td> <td>44,3</td> </tr> <tr> <td>2 1/2"</td> <td>63,5</td> <td>91</td> <td>52</td> <td>63,5 x 1,6</td> <td>60,3</td> <td>60,3 x 2</td> <td>56,3</td> </tr> </tbody> </table>	ASME BPE	BS4825 - ISO 1127	For tubes according to:				ASME BPE		ISO 1127		NPS	DN	PN bar	D	dM	Tube Male ø	Tube Female ø	Tube Male ø	Tube Female ø	40	3/4"	20	25,4	16	19,05 x 1,2	16,65	26,9 x 1,6	23,7	1"	25	50,5	21	25,4 x 1,6	22,2	33,7 x 2	29,7	1 1/2"	38	64	30	38,1 x 1,6	34,8	42,4 x 2	38,4	2"	51	77,5	38	50,8 x 1,6	47,5	48,3 x 2	44,3	2 1/2"	63,5	91	52	63,5 x 1,6	60,3	60,3 x 2	56,3
					ASME BPE	BS4825 - ISO 1127	For tubes according to:				ASME BPE		ISO 1127																																																	
NPS	DN	PN bar	D	dM			Tube Male ø	Tube Female ø	Tube Male ø	Tube Female ø																																																				
40	3/4"	20	25,4	16	19,05 x 1,2	16,65	26,9 x 1,6	23,7																																																						
	1"	25	50,5	21	25,4 x 1,6	22,2	33,7 x 2	29,7																																																						
	1 1/2"	38	64	30	38,1 x 1,6	34,8	42,4 x 2	38,4																																																						
	2"	51	77,5	38	50,8 x 1,6	47,5	48,3 x 2	44,3																																																						
	2 1/2"	63,5	91	52	63,5 x 1,6	60,3	60,3 x 2	56,3																																																						
20 21	<p>VARIVENT</p>	<table border="1"> <thead> <tr> <th>DN (d)</th> <th>PN bar</th> <th>suitable for In Line housing</th> <th>dM</th> </tr> </thead> <tbody> <tr> <td>50</td> <td>25</td> <td>DN25</td> <td>30</td> </tr> <tr> <td>68</td> <td>16</td> <td>DN40 and up</td> <td>46</td> </tr> </tbody> </table>	DN (d)	PN bar	suitable for In Line housing	dM	50	25	DN25	30	68	16	DN40 and up	46																																																
			DN (d)	PN bar	suitable for In Line housing	dM																																																								
50	25	DN25	30																																																											
68	16	DN40 and up	46																																																											